



Universal forseglingsfilm 42 µm til PP/PET-forme 185 mm x 400 m Transparent, 1 Stk/kart (1 x 1 Stk)

Vores universelle forseglingsfilm er det bedste valg, når du har brug for en film, der kan forsegle flere forskellige typer materialer, for eksempel PP, PET og PE. Den kan bruges ved temperaturer op til 180 grader.

- Kan forsegle de fleste typer materialer

Artikeloplysninger

Artikelnummer	159848	Fødevaregodkendelse	✓
Mærke	DUNI		
Undermærke	DUNIFORM®		
Materialekvalitet	Flerlags plastik		
Oprindelsesland	Holland		
Sæson	Året rundt		

Certificeringer

Tilbehør

Logistikoplysninger for 159848

Toldkode	39211900
----------	----------

Forbrugerenheder (CU)

Styk pr. CU	1
CU-bruttovægt (g)	3.100
CU-pakkevægt (g)	5
Længde x Bredde x Højde (mm)	177 x 177 x 185
CU-volumen (dm ³)	5
CU-stregkodenr.	

Salgs-/forsendelsesenheder (SKU)

CU pr. SKU	1
SKU-bruttovægt (g)	3.402
SKU-pakkevægt (g)	302
Længde x Bredde x Højde (mm)	195 x 195 x 190
SKU-volumen (dm ³)	7
SKU-stregkodenr.	



07321031598483

Palle

SKU pr. lag	24
SKU pr. ladning	120
Ladningsbruttovægt (kg)	429
Længde x Bredde x Højde (mm)	1.200 x 800 x 1.100
Ladningsvolumen (dm ³)	1.056

Dokumenter

https://mediabank.duni.com/doc/159848_DoC_en.pdf

https://mediabank.duni.com/doc/159848_PI_en.pdf

Vi står klar til at hjælpe.
Support og bestilling:
Opkald: +45 4484 8422
E-mail: info@duni.dk

DUNI
GROUP

ENVIRONMENTAL AND PRODUCT SAFETY DATA SHEET

Product

Seal film Universal/Multi for PET- and PP trays

Raw Material

PET/Nylon (Polyamide)/LDPE

Packaging

Inner: Polyethylene (PE)
Outer: Corrugated board box

Field Of Application

The product can be used safely with all types of foodstuffs for long term storage at room temperature and up to 180°C for 30 minutes.

The product can be used in a microwave oven.

EC Directive 94/62/EC on Packaging and Packaging Waste

The packaging complies with all essential requirements as defined by 94/62/EC.

For example minimum adequate amount of packaging, limitation of heavy metal content, recyclable through at least one of the following: reuse, material recovery, energy recovery or composting.

Environmental Aspects

Product

The plastics in the film are manufactured from fossil oil.

Packaging

Polyethylene is produced from fossil oil and the corrugated board box is made from wood, which is a renewable resource.

Product Safety

The products fulfil the following:

- EU Regulation 10/2011/EC with amendments
- EU Regulation 1935/2004/EC

- EU Regulation 2023/2006/EC
- Migration tests on the article material performed by an independent institute showed that under appropriate test conditions, overall and specific (when relevant) migration falls considerably below the limit given by regulation 10/2011. (For further details, see *Declaration of Compliance*).
- Duni manufacturing units are certified according to the international quality system ISO 9001. They have also implemented the environmental management system ISO 14001.

Processing & Storage

- Sealing temperature of 140°C-210°C, depending on the sealing layer.
- Recommended storage conditions: 15°C -25°C in a dry place, away from direct sunlight.
- Maximum storage time from point of unloading of goods to be 12 months, if stored as recommended.

Management of Used Products

Energy Recovery

All the materials are suited for energy recovery. Complete combustion gives mainly rise to carbon dioxide and water. The energy content of plastics/paper is comparable to that of oil/ wood.

Recycling

Recycling of the plastic and the corrugated board is possible for producing new products. Check with the local recycling company.

Validity

This is a copy of a document issued 2021-12-14. It is normally updated every second year or when there is a change in the manufacturing process, in the product or in legislation. To make sure that you have the latest edition, contact Duni Group.